



1/4"-20 SS INSERT LOCATIONS

UN MARKING READS:

31H2/Y/ / /USA
SNYDER IND. INC.
LINCOLN, NE 4462 / 2479
CAPACITY - 1249 LITERS
TARE MASS - KG
GAUGE TEST PRESSURE - 100 KPA
LAST LEAKPROOFNESS TEST - /
LAST INSPECTION - /

SNYDER INDUSTRIES, INC U.N. MARKED CONTAINER CLOSURE NOTIFICATION.
 ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE.
 ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A ± 3% TOLERANCE.

STANDARD 330 SQUARE STACKABLE "STANDARD PACKAGE OF EQUIPMENT"

7	1		STD IBC ASSEMBLY KIT W/BAG
6	1		ASM VENT PE 2IN VACUUM SII W/EPDM
5	1		ASM CAP PE 6IN H.DUTY 2IN NPT-EPDM W/TIE
4	2		ASM PLUG 2IN NPS BUNG W/EPDM-WHITE
3	1		ASM VALVE 2IN 4-BOLT STUBBY 100KPA
2	1		ASM BASE SQ STK 4WAY HD/RED
1	1		ASM TK 330 SQ HD/NAT BDR 2RB/3INS 6CAP
ITEM NO.	QTY.	PART NUMBER	DESCRIPTION
STATUS: Released		DO NOT SCALE	DRAWN BY: ET3
© SNYDER INDUSTRIES INC., 2015			TITLE: ASM TK 330 SQ NAT 2RB/3INS 6C P-RED EPDM
ALL DIMENSIONS, DESIGNS, AND INFORMATION ON THIS PRINT MUST BE CONSIDERED PROPRIETARY TO SNYDER INDUSTRIES, INC. AND MAY NOT BE USED, COPIED, OR DISTRIBUTED WITHOUT WRITTEN PERMISSION OF AN OFFICER (OR HIS AGENT) OF THE FIRM.			REVISION: A
PART NO.			ENG. ID.
			SHEET 1 OF 1